

IN THE CLAIMS:

The text of all pending claims (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~striketrough~~. When strikethrough cannot easily be perceived, or when five or fewer characters are deleted, [[double brackets]] are used to show the deletion. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

Please AMEND claims 1, 5, 9, 10, 16, 19, 25 and 26, and CANCEL claims 3 and 15 without prejudice or disclaimer in accordance with the following:

1. (CURRENTLY AMENDED) A pulley fixing apparatus for an image forming apparatus including a frame, a driving motor, and a power-transmitting belt driven by the driving motor and a driving pulley, the pulley fixing apparatus comprising:
 - a pulley fixing part rotatably fixing a driven pulley on the frame;
 - a sliding part movably supporting the pulley fixing part on the frame; and
 - an automatic tension adjusting part including an elastic pulling spring disposed between the pulley fixing part and the frame to elastically bias the pulley fixing part in a first direction and impart a predetermined tension to the power-transmitting belt, wherein:
 - the pulley fixing part comprises a first fixing portion;
 - the frame comprises a second fixing portion arranged between the first fixing portion and the driven pulley; and
 - the elastic pulling spring has one end fixed at the first fixing portion and another end fixed at the second fixing portion to push the driven pulley outwardly from the second fixing portion of the frame,

wherein:

 - the sliding part comprises a slide protrusion positioned at the pulley fixing part; and
 - the frame has an L-shaped protrusion guide hole positioned to support, receive and guide a projection of the slide protrusion.

2. (ORIGINAL) The apparatus according to claim 1, wherein the pulley fixing part comprises:
 - a plate member having a driven pulley support supporting the driven pulley and exposing a circumference surface of the driven pulley that contacts the power-transmitting belt to ease installation and removal of the power-transmitting belt.

3. (CANCELED)

4. (ORIGINAL) The apparatus according to claim 1, wherein:
the sliding part comprises first, second, third, and fourth slide protrusions positioned at the pulley fixing part; and
the frame has corresponding first, second, third, and fourth protrusion guide holes positioned to receive and guide the respective slide protrusions.

5. (CURRENTLY AMENDED) The apparatus according to claim ~~3~~1, wherein:
the protrusion guide hole has a length such that when the power-transmitting belt is not installed, the pulley fixing part is movable between a spring assembling position and an initial pulley fixing part-assembling position.

6. (ORIGINAL) The apparatus according to claim 5, wherein:
a length range of the power-transmitting belt is defined along the first direction from the driving pulley;
the spring assembling position is beyond the length range of the power-transmitting belt;
and
the initial pulley fixing part-assembling position is within the length range of the power transmitting belt.

7. (PREVIOUSLY PRESENTED) The apparatus according to claim 6, wherein:
a power-transmitting belt assembling position of the pulley fixing part is located between the length of range of the power-transmitting belt and the initial pulley fixing part-assembling position.

8. (ORIGINAL) The apparatus according to claim 6, wherein:
a tension adjusting position of the pulley fixing part is located between the spring assembling position and the initial pulley fixing part-assembling position, within the length range of the power-transmitting belt.

9. (CURRENTLY AMENDED) The apparatus according to claim ~~3~~1, wherein:
the projection of the slide protrusion comprises a projection having a support portion and a sliding end; and
the protrusion guide hole comprises a first lateral hole portion receiving the sliding end, and a second lateral hole portion receiving and guiding the support portion, wherein the second lateral hole portion is narrower than the first lateral hole portion.

10. (CURRENTLY AMENDED) The apparatus according to claim 9, wherein:
the support portion protrudes approximately perpendicularly from the pulley fixing part;
and
the sliding end protrudes approximately perpendicularly from the support portion; ~~and~~
~~the protrusion guide hole is approximately L-shaped.~~

11. (PREVIOUSLY PRESENTED) The apparatus according to claim 9, wherein
the slide protrusion further comprises:
a stopper preventing the sliding end from freely passing through the first lateral hole
portion after the sliding part is movably supported on the frame.

12. (PREVIOUSLY PRESENTED) The apparatus according to claim 11,
wherein the stopper comprises:
an L-shaped recess positioned at the sliding end to engage a sidewall of the first lateral
hole portion and a rear surface of the frame in a vicinity of the sidewall of the first lateral hole
portion.

13. (CANCELLED)

14. (PREVIOUSLY PRESENTED) The apparatus according to claim 1,
wherein:
the first fixing portion comprises a first hook positioned at the one end of the elastic
spring, and a first fixing protrusion to fix the first hook positioned at the pulley fixing part; and
the second fixing portion comprises a second hook positioned at the other end of the
elastic spring, and a second fixing protrusion to fix the second hook positioned at the frame to
protrude through a penetrated hole positioned at the pulley fixing part.

15. (CANCELED)

16. (CURRENTLY AMENDED) A pulley fixing apparatus for an image forming
apparatus including a frame, a driving motor, and a power-transmitting belt driven by the driving
motor and a driving pulley, the pulley fixing apparatus comprising:
a pulley fixing part rotatably fixing a driven pulley on the frame;
a sliding part movably supporting the pulley fixing part on the frame; and
an automatic tension adjusting part including an elastic pulling spring disposed between

the pulley fixing part and the frame to elastically bias the pulley fixing part in a first direction and impart a predetermined tension to the power-transmitting belt and an anti-release portion to prevent the pulley fixing part from being released from the frame by an external force of predetermined magnitude. ~~The apparatus according to claim 15,~~ wherein the anti-release portion comprises a second hook having a width that is greater than a width of the penetrated hole, and wherein:

the pulley fixing part comprises a first fixing portion;

the frame comprises a second fixing portion arranged between the first fixing portion and the driven pulley; and

the elastic pulling spring has one end fixed at the first fixing portion and another end fixed at the second fixing portion to push the driven pulley outwardly from the second fixing portion of the frame.

17. (PREVIOUSLY PRESENTED) An image forming apparatus having a pulley fixing apparatus, wherein the pulley fixing apparatus includes a frame, a driving motor, and a power-transmitting belt driven by the driving motor and a driving pulley, the image forming apparatus comprising:

the pulley fixing apparatus, wherein the pulley fixing apparatus further comprises:

a pulley fixing part rotatably fixing a driven pulley on the frame;

a sliding part movably supporting the pulley fixing part on the frame; and

an automatic tension adjusting part including an elastic pulling spring disposed between the pulley fixing part and the frame to elastically bias the pulley fixing part in a first direction and impart a predetermined tension to the power-transmitting belt wherein said driven pulley is pushed from an inside of said belt when the spring is in tension, wherein:

the pulley fixing part comprises a first fixing portion;

the frame comprises a second fixing portion arranged to push the driven pulley outwardly from the first fixing portion of the pulley fixing part; and

the automatic tension adjusting part comprises an elastic spring having one end fixed at the first fixing portion and another end fixed at the second fixing portion,

wherein the image forming apparatus is an inkjet printer, and wherein:

the power-transmitting belt comprises a power-transmitting belt transmitting a driving force to a feed roller in the inkjet printer;

the driving motor comprises a feed roller driving motor in the inkjet printer; and

the driven pulley comprises a power-transmitting pulley, transmitting the driving force of the feed roller driving motor through the power-transmitting belt.

18. (PREVIOUSLY PRESENTED) An image forming apparatus having a pulley fixing apparatus, wherein the pulley fixing apparatus includes a frame, a driving motor, and a power-transmitting belt driven by the driving motor and a driving pulley, the image forming apparatus comprising:

- the pulley fixing apparatus, wherein the pulley fixing apparatus further comprises:
 - a pulley fixing part rotatably fixing a driven pulley on the frame;
 - a sliding part movably supporting the pulley fixing part on the frame; and
 - an automatic tension adjusting part including an elastic pulling spring disposed between the pulley fixing part and the frame to elastically bias the pulley fixing part in a first direction and impart a predetermined tension to the power-transmitting belt wherein said driven pulley is pushed from an inside of said belt when the spring is in tension, wherein:
 - the pulley fixing part comprises a first fixing portion;
 - the frame comprises a second fixing portion arranged to push the driven pulley outwardly from the first fixing portion of the pulley fixing part; and
 - the automatic tension adjusting part comprises an elastic spring having one end fixed at the first fixing portion and another end fixed at the second fixing portion,
- wherein the image forming apparatus is an inkjet printer, and wherein:
 - the power-transmitting belt comprises a carrier belt transmitting a driving force to a print head of the inkjet printer;
 - the driving motor comprises a carrier driving motor of the inkjet printer; and
 - the driven pulley transmits the driving force of the carrier driving motor through the carrier transfer belt.

19. (CURRENTLY AMENDED) A pulley fixing apparatus for an image forming apparatus including a frame, a driving motor, and a power-transmitting belt driven by the driving motor and a driving pulley, the pulley fixing apparatus comprising:

- a pulley fixing part rotatably fixing a driven pulley on the frame;
- a sliding part movably supporting the pulley fixing part on the frame;
- an automatic tension adjusting part disposed between the pulley fixing part and the frame to elastically bias the pulley fixing part in a first direction and impart a predetermined tension to the power-transmitting belt; and
- a locking part to lock the pulley fixing part after the tension of the power-transmitting belt installed on the driven pulley is adjusted, wherein:
 - the pulley fixing part comprises a first fixing portion;
 - the frame comprises a second fixing portion arranged between the first fixing portion and the driven pulley; and

the automatic tension adjusting part comprises an elastic spring having one end fixed at the first fixing portion and another end fixed at the second fixing portion to push the driven pulley outwardly from the second fixing portion of the frame,

wherein:

the sliding part comprises a slide protrusion positioned at the pulley fixing part; and

the frame has an L-shaped protrusion guide hole positioned to support, receive and guide a projection of the slide protrusion.

20. (ORIGINAL) The apparatus according to claim 19, wherein the locking part comprises:

an elongated adjusting-guide with a long axis oriented at the pulley fixing part along the direction in which the pulley fixing part is elastically urged;

a threaded hole positioned at the frame to correspond to the elongated adjusting-guide hole; and

a locking screw engaging the threaded hole through the elongated adjusting-guide hole.

21. (ORIGINAL) The apparatus according to claim 20, wherein the locking part further comprises:

an anti-push portion to prevent the pulley fixing part from being pushed by the driving force of the power-transmitting belt.

22. (ORIGINAL) The apparatus according to claim 21, wherein the anti-push portion comprises:

at least one projection positioned at the frame in the vicinity of the threaded hole.

23. (ORIGINAL) The apparatus according to claim 22, wherein the projection comprises:

a protrusion portion positioned by press machining to protrude toward the pulley fixing part.

24. (ORIGINAL) The apparatus according to claim 23, wherein the projection comprises:

a burr positioned around a hole created by press machining, to protrude toward the pulley fixing part.

25. (CURRENTLY AMENDED) A subassembly of an image forming apparatus

including a frame, a driving motor, and a power-transmitting belt driven by the driving motor and a driving pulley, the subassembly comprising:

a pulley fixing part slidably fixing a driven pulley on the frame that imparts a tension to the power-transmitting belt by the driven pulley pushing from an inside of the belt when a spring disposed between the pulley fixing part and the frame is in tension, wherein:

the pulley fixing part comprises a first fixing portion;

the frame comprises a second fixing portion arranged between the first fixing portion and the driven pulley; and

the spring has one end fixed at the first fixing portion and another end fixed at the second fixing portion to push the driven pulley outwardly from the second fixing portion of the frame,

wherein:

a sliding part comprises a slide protrusion positioned at the pulley fixing part; and

the frame has an L-shaped protrusion guide hole positioned to support, receive and guide a projection of the slide protrusion.

26. (CURRENTLY AMENDED) A pulley fixing apparatus for an image forming apparatus including a frame, a driving motor, a power-transmitting belt driven by the driving motor and a driving pulley, the pulley fixing apparatus comprising:

an assembly positioned inside the belt and comprising:

a pulley fixing part rotatably fixing a driven pulley on the frame;

a sliding part movably supporting the pulley fixing part on the frame; and

an automatic tension adjusting part disposed between the pulley fixing part and the frame to elastically bias the pulley fixing part in a first direction and impart a predetermined tension to the power-transmitting belt when a spring disposed between the pulley fixing part and the frame is in tension, wherein:

the pulley fixing part comprises a first fixing portion;

the frame comprises a second fixing portion arranged between the first fixing portion and the driven pulley; and

the spring has one end fixed at the first fixing portion and another end fixed at the second fixing portion to push the driven pulley outwardly from the second fixing portion of the frame,

wherein:

the sliding part comprises a slide protrusion positioned at the pulley fixing part; and

the frame has an L-shaped protrusion guide hole positioned to support, receive and guide a projection of the slide protrusion.